

#### Leica DISTO™ D110 & D2





















The original laser distance meter

Leica DISTO™ D110 & D2

### Leica DISTO™ D110

## Small size – great possibilities



#### Always at hand

The removable pocket clip is a clever accessory for carrying the Leica DISTO™ D110 on your clothing. Use it to attach the unit to your trousers, shirt or jacket so that you have it always at hand.



#### Small and handy

The Leica DISTO™ D110 is the smallest and lightest laser distance meter in the DISTO™ product range. With an ergonomic shape, it fits perfectly into your hand and is effortless to use. The self-explanatory keys ensure operation is quick and intuitive.

## Bluetooth® Smart and Leica DISTO™ Sketch app



#### Extended functionality by pressing a button

The smart App "Leica DISTO™ sketch" is the ideal link between the Leica DISTO™ with Bluetooth® Smart and a smartphone or a tablet. It allows you to create and precisely dimension sketches and pictures. The files can then be sent directly to the office. This simplifies and speeds up work flow.

### Leica DISTO™ D2

## Many functions - long range

#### Multifunctional end piece

Whether you are taking measurements from corners, grooves or edges, with the multifunctional end piece you can always accurately position the Leica DISTOTM D2. The position of the end piece is automatically detected and taken into account. This prevents expensive measuring errors.



# Versatile thanks to useful measuring functions

Functions such as addition and subtraction, area and volume calculations make every measurement task child's play. The instrument stores the last 10 measurement results.



Free app: Leica DISTO™ sketch









| Technical data           | DISTO™ D110  | DISTO™ D2        |
|--------------------------|--|------------------|
| Typ. measuring accuracy  | ± 1.5 mm   | ± 1.5 mm         |
| Range                    | 0.2 up to 60 m                                       | 0.05 up to 100 m |
| Measuring units          | m, ft, in  | m, ft, in        |
| X-Range Power Technology | •  | •                |
| Display illumination     | •  | •                |
| Free App                 | •  | •                |
| Data interface*          | Bluetooth® Smart                                     |                  |
| Battery life time**      | up to 10,000 measurements<br>up to 20 h of operation |                  |
| Batteries                | type AAA, 2 × 1.5 V                                  |                  |
| Protection class         | IP 54 (dust and splash water protected)              |                  |
| Dimensions               | 120 × 37 × 23 mm                                     | 116 x 44 x 26 mm |
| Weight with batteries    | 92 g   | 100 g            |




<sup>\*\*)</sup> Reduced in Bluetooth® Smart mode

| Functions              | DISTO™ D110 | DISTO™ D2  |
|------------------------|-------------|------------|
| Distance measurement   | •           | •          |
| Addition / subtraction | 0           | •          |
| Area measurements      | •           | •          |
| Volume measurement     | 0           | •          |
| Memory                 | 0           | 10 results |
| Automatic end piece    | 0           | •          |

PROTECT is subject to Leica Geosystems International Limited Warranty and PROTECT General Terms & Conditions set out under www.leica-geosystems.com/protect.

<sup>\*</sup> Available through free online registration within 8 weeks from the purchase date.











Laser class 2 in accordance with IEC 60825-1

