Leica DISTO™ X310

The original laser distance meter



Robust multifunctionality!

The new Leica DISTO™ X310 is the only laser distance meter to be dust-tight and protected against water jets - to IP65. In addition, it passes drop tests of up to 2 m height. Thanks to the integrated tilt sensor, it can take indirect distance and height measurements absolutely precisely.

Leica DISTO™ X310 - guarantees reliable measurements, even under the harshest conditions.

Featured with:

- IP65 water jet protection and dust-tight
- 360° tilt sensor
- Smart Horizontal Mode™
- Height tracking
- Power Range Technology™
- Illuminated 4-line display
- Automatic multifunctional end-piece





The sensitive measuring elements

are protected by solid rubber

parts. Proven in drop tests from up

to 2 m height, the Leica DISTO™

X310 is therefore particularly

Protection class IP65

The housing and keypad are specially sealed against water and dust. Cleaning under running water is also no problem.



Leica DISTO™ X310

Art.No. 790656

- Leica DISTO[™] X310 laser distance meter
- Holster
- Hand loop
- **Batteries**



Tilt sensor 360°

Robust housing

resistant.

Thanks to the combination of distance and tilt measurements, you can determine the horizontal distance absolutely precisely and simply - even past obstructions. With the help of the tilt sensor, you can also determine indirect heights.



Smart Horizontal Mode™

If obstructions prevent you from taking direct distance measurements, you can use the Smart Horizontal Mode™ to determine the horizontal distance simply and absolutely precisely.

Technical Data

I Common Data	
General	
Typical measuring	± 1 mm
accuracy	
Range	80 m
Measuring units	0.000 m, 0.0000 m,
-	0.00 m, 0.00 ft, 0'00"
	1/32, 0.0 in, 0 in 1/32
Power Range	•
_Technology [™]	
Distance in m	10, 50, 100 m
Ø of the laser dot in mm	6, 30, 60 mm
Protection class	IP65 – water jet
	protection and
	dust-tight
Measurements	up to 5000
per set of batteries	
Batteries	Type AAA 2 x 1,5 V
Dimensions	122 × 55 × 31 mm
Weight with batteries	155 g
Functions	
Min/max measurement	•
Continuous	•
measurement	
Stake out function	•
Addition/subtraction	•
Area/volume	•
Painter function	•
Pythagoras	3 points,
	partial height
Smart Horizontal Mode	•
Height tracking	•
Memory	20 Displays
Illuminated display	• •
Multifunctional	with automatic
end-piece	recognition

All illustrations, descriptions and technical specifications are subject to change without prior notice. Printed in Switzerland. Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012.

Leica Geosystems AG Heerbrugg, Switzerland www.leica-geosystems.com





Laser Class 2 In accordance with IEC 60825-1



Dealer Stamp





