aserline

VideoFlex G3 Ultra SnakeCamera G3 10m



Professional video inspection system for visually inspecting areas that are difficult to access – also over great distances

Rev 0915







Camera head (ø 9 mm) with LED-Lighting

VideoFlex G3 Ultra

ARTICLE

3.5" TFT colour display

ARTICLE NO.

DISPLAY

082.210A

- The camera head at a FlexCamera transfers pictures directly to a LCD-Monitor.
- Problem locating: the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- REC-Function: still picure and video can be recorded for a later analysis.
- Waterproof camera head and cable
- Ideal for difficult accessibly areas due to the small measuring head (ø 9 mm)
- Camera unit can be replaced to suit application
- Powerful object lighting thanks to 4 high-performance LEDs
- Extraneous light reduction: contrasty LC-Display which provides an optimum display even under light irridation.
- External monitors operated via **TV Out connection**
- Formattable SDHC-Card

EAN CODE

20 x 240

4 021563 695003

- Rotation: The manual image rotation function enables the image to be rotated by 180° on the monitor.
- Mirror function for correcting mirror-inverted images.

TECHNICAL DATA

CAMERA HEAD / CABLE ø 9 mm, IP 68 (immersion depth 2 m, 60 min.) CAMERA FOCUS F1 cm - F6 cm SCREEN TYPE 3.5" TFT colour display CAMERA RESOLUTION 640 x 480 pixel **RESOLUTION DISPLAY** 320 x 240 pixel **RESOLUTION PICTURE / VIDEO** 720 x 480 pixel FORMAT PICTURE / FORMAT VIDEO JPEG / AVI LED 10 luminosity degrees ZOOM 1.5 x digital zoom in 10% steps MEMORY Supports up to max. 8 GB SDHC card LENGTH OF FLEX CABLE 10 m PORT Mini USB **CONNECTIONS** Micro-SD, Analog-video POWER SUPPLY Li-lon pack battery 3.7V / 1.7Ah / 5V / 1A power supply unit CHARGING TIME approx. 4 h OPERATING TIME approx. 4 h OPERATING TEMPERATURE 0°C...45°C STORAGE TEMPERATURE -10°C ... 60°C WEIGHT (incl. batteries and flexcamera) 1.6 ka



VideoFlex G3 Ultra

inclusive carrying case + SnakeCamera G3 10 m

- + TopClips G3
- + TopGuide G3
- + Li-ion battery pack
- + Power supply unit/charger with internal adapter
- + USB cable
- + 4 GB micro-SD card + Video cable

Packing dimension (W x H x D) 450 x 375 x 125 mm

CAMERA 40 x 48

UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com

3.5" LCD

PU

2