

## VideoScope One



Compact inspection camera for visual inspections of areas which are difficult to access









 The camera head on the flexible cable transmits images directly to the LC monitor.

- Problem locating: the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- Waterproof camera head and cable
- Ideal for difficult accessibly areas due to the small measuring head (ø 9 mm)
- **Diversified application** with 1,5 m camera.
- Powerful object lighting thanks to
  4 high-performance LEDs
- Extraneous light reduction: contrasty
  LC-Display which provides an optimum display even under light irridation.
- External monitors operated via TV Out connection
- Rotation: The manual image rotation function enables the image to be rotated by 180° on the monitor.

## **TECHNICAL DATA**

CAMERA HEAD

ø 9 mm, waterproof, IP 67

CAMERA FOCUS F3 cm - F7 cm

SCREEN TYPE 2.7" TFT colour display

CAMERA RESOLUTION 320 x 240 pixel RESOLUTION DISPLAY 320 x 240 pixel

**LED** 5 luminosity degrees

**ZOOM** 2x digital zoom in 10% increments

LENGTH OF FLEX CABLE 1,5 m

POWER SUPPLY

4 x AA 1,5 Volt batteries

OPERATING TEMPERATURE 0 °C ... 45 °C STORAGE TEMPERATURE -10 °C ... 60 °C


WEIGHT (incl. batteries) 0,51 kg





VideoScope One + batteries

**Packing dimension** (W x H x D) 175 x 300 x 125 mm



CAMERA













