
Laserliner



Three-dimensional, practical laser with one horizontal and two vertical green laser circles, compact 150 cm tripod, and a comprehensive range of accessories — all you need for demanding projects




This three-dimensional, compact and highly visible green laser projects one horizontal and two vertical laser circles for precise alignment of objects. The laser crosses form a plumb function for working simultaneously on floors and ceilings. A manual slope mode is available for creating gradients. This laser is all you need for demanding projects thanks to the comprehensive range of accessories. Multi-section telescopic tripod legs and a 30 cm crank on this compact tripod provide an extensive adjustment range. The PocketWallHolder is a multi-functional, height-adjustable, magnetic bracket for attaching to walls, metal items and tripods with a 1/4" or 5/8" thread.



- Accurate horizontal and vertical alignment of
- · Good visibility through green laser technology
- Easy alignment of slopes with manual tilt function
- · Plumb function for synchronous working on floor and ceiling

ACCURACY ± 0 LEVELLING aut VISIBILITY (TYPICAL)* 30 WORKING RANGE WITH HAND RECEIVER affective brig LASER WAVELENGTH 51! LASER CLASS 2 / 608	pends on how the technology ects the difference in yhtness) 60 m
LEVELLING aut VISIBILITY (TYPICAL)* 30 WORKING RANGE WITH HAND RECEIVER affe brig LASER WAVELENGTH 51! LASER CLASS 2 / 608	omatic m pends on how the technology ccts the difference in yhtness) 60 m
VISIBILITY (TYPICAL)* 30 WORKING RANGE WITH HAND RECEIVER affice bright street wavelength 51! LASER WAVELENGTH 51! LASER CLASS 2 / 608	m pends on how the technology ects the difference in ghtness) 60 m
WORKING RANGE WITH HAND RECEIVER LASER WAVELENGTH LASER CLASS 2 / 608	pends on how the technology ects the difference in yhtness) 60 m
HAND RECEIVER afficient bright afficient	ects the difference in ghtness) 60 m
LASER CLASS 2 / 608	
608	5 nm
	< 1 mW (EN 325-1:2014/AC:2017)
	on battery pack 3.7V / 3.6Ah / 32Wh
OPERATING TIME with	h 3 laser levels: approx. 9 urs
rH, wo	50°C, max. humidity 80% no condensation, max. rking altitude 4000 m above level
	°C 70°C, max. humidity % rH
DIMENSIONS (W X H X D) 104	
WEIGHT 388	1 mm x 97 mm x 76 mm x #







max 40 m





























EAN-CODE 4021563725496

PU 1

