

ArcView Camera



Camera unit for VideoFlex with mechanically adjustable camera head

- Camera unit for VideoFlex
- Wheel for moving the camera head mechanically
- For inspecting highly inaccessible locations such as cavities, shafts, masonry or in vehicles
- Waterproof camera head and cable
- 4 high-performance LEDs for powerful object lighting at the camera
- Compatible with G3/G4

TECHNICAL SPECIFICATIONS

CAMERA TYPE	CMOS image sensor
CAMERA HEAD	ø 9 mm
CAMERA HEAD PROTECTION CLASS	water-resistant, IP 67
CAMERA HEAD LEDS	4
CAMERA RESOLUTION	640 x 480 pixels
FIELD OF VIEW (FOV)	57°
CAMERA FOCUS	F3 cm - F5 cm
CABLE DIAMETER	7,6 mm
LENGTH OF FLEX CABLE	1 m
MINIMUM BENDING RADIUS	100 mm
OPERATING CONDITIONS	0°C ... 45°C, max. humidity 20 ... 90% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS	-10°C ... 60°C, max. humidity 80% rH
DIMENSIONS (W X H X D)	1120 mm x 39 mm x 38 mm
WEIGHT	268 g

